

T40P

10/100Mb Ethernet

132 x 64 pixel graphical LCD with backlight

HD voice: HD Codec, HD Speaker, HD Handset

3 VoIP accounts, BLF/BLA, IPV6, Open VPN



Optima
HD Voice



Paperless

This stylish T40P is a feature-rich SIP phone ideal for everyday office users. The 10/100Mb telephone benefits from an intuitive interface, BLF's, HD Voice, 3-way conferencing, handsfree speakerphone and supports corded or wireless headset and EHS.

With simple flexible and secure provisioning options, the T40P is certified compatible with 3CX, Asterisk and BroadSoft.

T40P

Audio Features

HD voice: HD handset, HD speaker
Wideband codec: G.722
Narrowband codec: G.711(A/μ), G.729AB, G.726
DTMF: In-band, Out-of-band(RFC 2833) and SIP INFO
Full-duplex hands-free speakerphone with AEC
VAD, CNG, AEC, PLC, AJB, AGC

Phone Features

3 VoIP accounts
One-touch speed dial, redial
Call forward, call waiting
Call transfer, call hold
Call return, group listening, SMS
Mute, auto answer, DND
3-way conference call
Direct IP call without SIP proxy
Ring tone selection/import/delete
Hotline, emergency call
Set date time manually or automatically
Dial Plan
XML Browser
Action URL/URI
RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)

Directory

Local phonebook up to 1000 entries
Black list
XML/LDAP remote phonebook
Intelligent search method
Phonebook search/import/export
Call history: dialled/received/missed/forwarded

IP-PBX Features

Busy Lamp Field (BLF)
Bridged Line Appearance(BLA)
Anonymous call, anonymous call rejection
Hot-desking
Message Waiting Indicator (MWI)
Voice mail
Call park, call pickup
Intercom, paging
Music on hold
Call recording

Display and Indicator

2.3" 132x64-pixel graphical LCD with backlight
LED for call and message waiting indication
Dual-colour (red or green) illuminated LEDs for line status information
Intuitive user interface with icons and soft keys
National language selection
Caller ID with name, number

Feature keys

3 line keys with LED
5 features keys: message, headset, mute, redial, hands-free speakerphone
4 context-sensitive "soft" keys
6 navigation keys
2 volume control keys
Mute key
Headset key
Hands-free speakerphone key

Interface

2xRJ45 10/100M Ethernet ports
1xRJ9 (4P4C) handset port
1xRJ9 (4P4C) headset port
1XRJ12 (6P6C) EHS port
Power over Ethernet (IEEE 802.3af), Class 2

Other Physical Features

Stand with 2 adjustable angles
Wall mountable
External universal AC adapter (optional): AC 100~240V input and DC 5V/600mA output
Power consumption (PSU): 1.05-3.23W
Power consumption (PoE): 1.7-3.2W
Dimension(W*D*H*T): 212mm*189mm*175mm*54mm
Operating humidity: 10~95%
Operating temperature: -10~50°C

Management

Configuration: browser/phone/auto-provision
Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
Auto-provision with PnP
BroadSoft device management
Zero-sp-touch TR-069
Phone lock for personal privacy protection
Reset to factory, reboot
Package tracing export, system log

Network and Security

SIP v1 (RFC2543), v2 (RFC3261)
Call server redundancy supported

NAT transverse: STUN mode
Proxy mode and peer-to-peer SIP link mode
IP assignment: static/DHCP
HTTP/HTTPS web server
Time and date synchronization using SNTP
UDP/TCP/DNS-SRV(RFC 3263)
QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
SRTP for voice
Transport Layer Security (TLS)
HTTPS certificate manager
AES encryption for configuration file
Digest authentication using MD5/MD5-session
OpenVPN, IEEE802.1X
IPv6

Certifications




WEEE Compliant



ROHS Compliant



Hearing Aid Compatible



...and many more

Yealink

EASY VoIP